

# **Spartan Chemical Company, Inc. Material Safety Data Sheet**

# **SECTION I: PRODUCT INFORMATION**

Product Name or Number (as it appears on label): SHINELINE EMULSIFIER PLUS

Product Division: Janitorial

R. Janus Supply Co. [810] 985-9757 614 Huron Ave. Port Huron, MI 48060

1110 Spartan Drive Maumee OH 43537

Spartan Chemical Company, Inc.

Product Number: 0084

Jannon an Product/Technical1-(800)-537-8990 Information: Medical Emergency:1-(888)-314-6171 (24 hours) Chemical Leak/SpilCHEMTREC 1-(800) 424-9300 (24 hours) Fmergency: Medical Emergency:1-(888)-314-6171 (24 hours)

Shipping Description: Corrosive liquids, n.o.s., 8, UN 1760, II, (contains sodium hydroxide) **NFPA Ratings: HMIS Ratings:** Health: 3 - Serious Health: \*3 - Serious; Chronic Hazard Fire: 0 - Minimal Fire: 0 - Minimal Reactivity: 0 - Minimal Reactivity: 0 - Minimal Pers. Prot. Equip.: See Section VIII

### <sup>₩</sup> SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

	% W	CAS Registry No.	Table Z- 1 - A			NTP, IARC or
Chemical Name(s)			TWA mg/m <sup>3</sup>	STEL mg/m <sup>3</sup>	CELING mg/m <sup>3</sup>	OSHA Carcinogen
*2-Butoxyethanol	20-30	111-76-2	120 (skin)	Not Established	Not Established	No
Monoethanolamine	5-10	141-43-5	6	15 (ACGIH)	Not Established	No
Sodium xylene sulfonate	1-5	1300-72-7	Not Established	Not Established	Not Established	No
Sodium metasilicate	1-5	6834-92-0	Not Established	Not Established	Not Established	No
Sodium hydroxide	1-5	1310-73-2	2	Not Established	Not Established	No
Ethoxylated alcohols phosphate ester	1-5	68130-47-2	Not Established	Not Established	Not Established	No

Comment: \*This substance is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (SARA) and of 40 CFR 372.

### **SECTION III: PHYSICAL DATA**

Boiling Point: 200 °F		Vapor Pressure:	Unknown	
	Vapor Density (AIR = 1):	Unknown	Solubility in Water:	Complete
	pH:-	13. 5-13.7	Specific Gravity (H <sub>2</sub> O=1):	1.02
;,,	Evaporation Rate (but.ace.=1):	<1	Percent Solid by Weight:	8-9
	Physical State:	Liquid	a menanen er i Urelle R <sub>ese</sub> nen mener er en en Kilk gegen er onna er med -folde <sub>ster en g</sub> un omnanen ser	
p = -/- A1-	Appearance & Odor:	Clear liqui d, fresh fragrance	,, , , , , , , , , , , , , , , , ,	

### <sup>™</sup> SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point: > 200°F	Method Used: ASTM-D56			
Flammable Limits: N/A	Flame Extension: N/A			
Extinguishing Media: Carbon dioxide, dry chemical, synthetic foam or water.				
Special Fire Fighting Procedures: Wear NIOSH approved self-contained breathing apparatus and protective clothing. Cool fire-exposed containers with water spray.				
Unusual Fire & Explosive Hazards: Combustion products are toxic.				

*** SECTION V: HEALTH HAZA	RD DATA			
Threshold Limit Value:	Not Estab lished	Primary Routes of Entry: Inhalation, Skin Contact, Eyes & Oral		
Effects of Overexposure-	CORROSI VE:			
Conditions to Avoid:	<ul> <li>HARMFUL TO EYES: Causes severe eye damage or irritation with symptoms of pain, redness, swelling of the conjunctiva and possible permanent corneal damage.</li> <li>HARMFUL TO SKIN: Causes severe skin damage or irritation with symptoms of pain, redness and chemical burns. Harmful contact may not cause immediate pain. Repeated contact may cause a dermatitis. Harmful if absorbed through the skin.</li> <li>HARMFUL OR FATAL IF SWALLOWED: Causes damage or chemical burns to esophagus and mucous membranes with symptoms of pain, nausea, vomiting and diarrhea. Aspiration of product into the lungs may occur during ingestion or vomiting, resulting in lung injury.</li> <li>HARMFUL IF INHALED: Breathing product vapor or mist may cause irritation or damage of the respiratory tract, with symptoms of nasal discomfort and discharge with chest pain and coughing. Contains 2-butoxyethanol which may cause central nervous system depression with symptoms such as headache; dizziness; nausea and drowsiness. Exposure to 2-butoxyethanol may cause blood cell; liver and kidney damage based on animal data.</li> <li>Contains monoethanolamine which may cause liver and kidney damage with repeated exposure.</li> <li>Do not get in eyes, on skin or clothing. Avoid breathing product vapor or mist. Do not swallow.</li> </ul>			
Conditions Aggravated by Use:	Use of this pro duct may aggravate pro dermatitis.	eexisting skin; eye and respiratory disorders including asthma and		
Emergency & First Aid Procedures	an an an tao an tao ana ana ana ana ana ana ana ana ana a			
Eyes:	Im mediately flush eyes with plenty of poison control center or doctor for tre	f water for at least 15 minutes. Remove contact lenses. Call a catment advice.		
Skin:		water for at least 15 minutes while removing contaminated trol center or doctor for treatment advice. wash contaminated ninated shoes.		
Ingestion:		immediately for treatment advice. Do not induce vomiting. Drink product. Do not give anything by mouth to an unconscious person.		
Inhalation:		ziness; move person to fresh air. If not breathing; give artificial ive oxygen. Call a poison control center or doctor for treatment		

# SECTION VI: REACTIVITY DATA

Stability: Stable	Incompatible Materials: Strong acids and oxidizing agents
Hazardous Decomposition Products: None known	Hazardous Polymerization: Will Not Occur

### <sup>W</sup> SECTION VII: SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Contain large spills and transfer the material to appropriate containers for reclamation or disposal. Material is Released or Spilled: Absorb remaining material or small spills with an inert material and dispose of in accordance with federal, state and local regulations. Keep spill out of sewers streams or other bodies of water. Waste Disposal Method: As sure conformance with federal, state and local regulations.

# <sup>397</sup> SECTION VIII: SPECIAL PROTECTION INFORMATION

	Not n ormally required when good general ventilation is provided. However if exposure limits are exceeded (see Section II) or if respiratory irritation occurs, the use of a NIOSH approved respirator suitable for the use-conditions and chemicals listed in Section II should be considered.
Ventilation:	Pr ovide good general ventilation. Local exhaust ventilation may be necessary for some operations.
Protective Gloves(Specify Type):	Solvent/alkali res istant gloves such as neoprene, nitrile or natural rubber/ latex are recommended.
Eye Protection(Specify Type):	Splash goggles are recommended to prevent eye contact.
Other Protective Equipment:	Solvent /alkali resistant boots are recommended. Use of impervious apron, face shield and other protective equipment should be considered in order to prevent or minimize contact with this product. Eye wash stations and washing facilities should be readily accessible. See 29 CFR 1910.132-138.

# <sup>W</sup> SECTION IX: SPECIAL PRECAUTIONS

Precautions; Handling & Storing	Keep container t ightly closed. Store in a cool, dry area. Do not freeze. Do not store above 120°F. Do not mix with other chemicals.				
Other Precautions	: Keep out of rea	ich of children.		2012 1990 1991 1997 1997 1997 1997 1997 1997	
© SCC 01/05/2006	Name:	Ronald T. Cook	Title:	Manager, Regulatory Affairs	
SHINELINE EMULSIFIER PLU	S Effective Date:	01/05/2006	Supercedes:	06/30/2005	
Ref: 29 CFR 1910.1200 (OSHA)	Changes:	Update Sections II, V, & VIII			
This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied,					
as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to					
evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and					
regulations.					

R. Janus Supply Co. [810] 985-9757. 614 Huron Ave. Port Huron, MI 48060