## Safety Data Sheet



## SECTION 1: Product and company identification

Product name : DS Insect Repellent

Use of the substance/mixture : Aerosol

Pest control products - Insect repellents

Product code : 841501

Company : Share Corporation

P.O. Box 245013

Milwaukee, WI 53224 - USA

T (414) 355-4000

Emergency number : Chemtrec: (800) 424-9300

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

## Classification (GHS-US)

Flam. Aerosol 2 H223 Compressed gas H280 Skin Irrit. 2 H315 Eye Irrit. 2A H319

Full text of H-phrases: see section 16

#### 2.2. Label elements

#### **GHS-US** labeling

Hazard pictograms (GHS-US)



 $\Diamond$ 



GHS02

GHS04

GHS07

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : Flammable aerosol

Contains gas under pressure; may explode if heated

Causes skin irritation

Causes serious eye irritation

Precautionary statements (GHS-US) : Keep away from heat, hot surfaces, open flames, sparks. - No smoking

Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use

Wash thoroughly after handling

Wear eye protection, face protection, protective clothing, protective gloves

If on skin: Wash with plenty of water

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing

If skin irritation occurs: Get medical advice/attention
If eye irritation persists: Get medical advice/attention
Take off contaminated clothing and wash before reuse

Store in a well-ventilated place

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

#### 2.3. Other hazards

No additional information available

## 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/information on ingredients

## 3.1. Substance

Not applicable

Full text of H-phrases: see section 16

## 3.2. Mixture

Sim Milatui C			
Name	Product identifier	%	Classification (GHS-US)
2-propanol	(CAS No) 67-63-0	15 - 40	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

Date of issue: 9/1/2015 Revision date: 05/05/2015 Version: 1.0 P GHS SDS Page 1 of 7

## Safety Data Sheet



Name	Product identifier	%	Classification (GHS-US)
Petroleum gases, liquefied	(CAS No) 68476-86-8	10 - 30	Flam. Gas 1, H220 Compressed gas, H280 Muta. 1B, H340 Carc. 1A, H350
N,N-diethyl-m-toluamide, deet	(CAS No) 134-62-3	22.56	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
acetone, propan-2-one, propanone	(CAS No) 67-64-1	3 - 7	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
ETHYLHEXYLBICYCLOHEPTENE DICARBOXIMIDE	(CAS No) 113-48-4	5	Not classified
DIPROPYL PYRIDINEDICARBOXYLATE	(CAS No) 136-45-8	2.5	Not classified

## **SECTION 4: First aid measures**

4.1. Description of first aid measures

First-aid measures after ingestion

First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Remove the victim into fresh air. Artificial respiration and/or oxygen if necessary.

First-aid measures after skin contact : Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Rinse mouth with water. Do not induce vomiting without medical advice. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes eye irritation. Causes serious eye irritation.

Symptoms/injuries after inhalation : None under normal use.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : Gastrointestinal complaints.

## 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## **SECTION 5: Firefighting measures**

5.1. Extinguishing media

Suitable extinguishing media : Dry chemical powder. Alcohol-resistant foam. Foam. Unsuitable extinguishing media : Solid water jet ineffective as extinguishing medium.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable aerosol.

Reactivity : Upon combustion: CO and CO2 are formed.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Do not breathe fumes from fires or vapors from

decomposition.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

## **SECTION 6: Accidental release measures**

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No flames, No sparks. Eliminate all sources of ignition. No naked lights. No smoking.

6.1.1. For non-emergency personnel

Protective equipment : Do not enter without an appropriate protective equipment.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

Take up liquid spill into inert absorbent material.

6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill. Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material.

**6.4.** Reference to other sections

No additional information available

Date of issue: 9/1/2015 Revision date: 05/05/2015 Version: 1.0 P GHS SDS Page 2 of 7

## Safety Data Sheet

# SHARE

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Keep away from heat, sparks and

flame

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Do not puncture, incinerate or crush.

Storage conditions : Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep cool. Protect from sunlight. Store in a

well-ventilated place. Store in a dry place.

Incompatible products : alkalis. strong acids. Strong oxidizers.

Storage area : Aerosol 2.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

2-propanol (67-63-0)			
ACGIH	ACGIH TWA (ppm)	200 ppm	
ACGIH	ACGIH STEL (ppm)	400 ppm	
ACGIH	Remark (ACGIH)	Eye & URT irr; CNS impair	
acetone, propan-2-one, propanone (67-64-1)			
ACGIH	ACGIH TWA (ppm)	250 ppm	
ACGIH	ACGIH STEL (ppm)	500 ppm	
ACGIH	Remark (ACGIH)	eye irr; CNS impair; BEI	

#### 8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Personal protective equipment : Safety glasses.



## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance : Aerosol. Clear, amber liquid.

Odor : characteristic
Odor threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : No data available

Boiling point : 165 °F

Flash point : No data available Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) No data available **Explosion limits** : No data available : No data available Explosive properties Oxidizing properties : No data available Vapor pressure : No data available Relative density No data available Relative vapor density at 20 °C No data available Specific gravity / density 0.87 g/ml Solubility No data available

Solubility : No data available
Log Pow : No data available
Log Kow : No data available
Auto-ignition temperature : No data available

Date of issue: 9/1/2015 Revision date: 05/05/2015 Version: 1.0 P GHS SDS Page 3 of 7

## Safety Data Sheet

Decomposition temperature : No data available Viscosity : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available : No data available

VOC content : 64.5 %

## SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Upon combustion: CO and CO2 are formed.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No additional information available

#### 10.4. Conditions to avoid

Aerosol containers are unstable at temperatures above 49°C. Avoid temperatures exceeding the flash point.

#### 10.5. Incompatible materials

Oxidizing agent. strong acids. alkalis.

#### 10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

## SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

N,N-diethyl-m-toluamide, deet (134-62-3)		
ATE CLP (oral)	500.000 mg/kg body weight	
2-propanol (67-63-0)		
LD50 oral rat	5045 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Experimental value; 5840 mg/kg bodyweight; Rat)	
LD50 dermal rabbit	12870 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402; 16.4; Rabbit)	
LC50 inhalation rat (mg/l)	73 mg/l/4h (Rat)	
ATE CLP (oral)	5045.000 mg/kg body weight	
ATE CLP (dermal)	12870.000 mg/kg body weight	
ATE CLP (vapors)	73.000 mg/l/4h	
ATE CLP (dust, mist)	73.000 mg/l/4h	

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified. Carcinogenicity : Not classified.

## 2-propanol (67-63-0)

IARC group 3 - Not Classifiable

Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified. Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : None under normal use.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : Gastrointestinal complaints.

## **SECTION 12: Ecological information**

### 12.1. Toxicity

2-propanol (67-63-0)

 Date of issue: 9/1/2015
 Revision date: 05/05/2015
 Version: 1.0
 P GHS SDS
 Page 4 of 7



## Safety Data Sheet



2-propanol (67-63-0)	
LC50 fish 1	4200 mg/l (96 h; Rasbora heteromorpha; Flow-through system)
EC50 Daphnia 1	> 10000 mg/l (48 h; Daphnia magna)
LC50 fish 2	9640 mg/l (96 h; Pimephales promelas; Lethal)
EC50 Daphnia 2	13299 mg/l (48 h; Daphnia magna)
Threshold limit algae 1	> 1000 mg/l (72 h; Scenedesmus subspicatus; Growth rate)
Threshold limit algae 2	1800 mg/l (72 h; Algae; Cell numbers)

### 12.2. Persistence and degradability

2-propanol (67-63-0)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	1.19 g O /g substance
Chemical oxygen demand (COD)	2.23 g O /g substance
ThOD	2.40 g O /g substance
BOD (% of ThOD)	0.49 % ThOD

#### 12.3. Bioaccumulative potential

2-propanol (67-63-0)	
Log Pow	0.05 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

## SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

No additional information available

Transport hazard class(es) (DOT)

## **SECTION 14: Transport information**

## **Department of Transportation (DOT)**

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950
Proper Shipping Name (DOT) : Aerosols

flammable, (each not exceeding 1 L capacity)

: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



Marine pollutant : Yes (IMDG only)



DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None DOT Special Provisions (49 CFR 172.102) : N82 DOT Packaging Exceptions (49 CFR : 306

173.xxx)

**DOT Quantity Limitations Passenger** 

aircraft/rail (49 CFR 173.27)

: 75 kg

DOT Quantity Limitations Cargo aircraft

only (49 CFR 175.75)

: 150 kg

5/11/ (45 O/ 10 175.75)

- Δ

DOT Vessel Stowage Location :

DOT Vessel Stowage Other : 25 - Shade from radiant heat,87 - Stow "separated from" Class 1 (explosives) except Division

14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

 Date of issue: 9/1/2015
 Revision date: 05/05/2015
 Version: 1.0
 P GHS SDS
 Page 5 of 7

## Safety Data Sheet



15 - 40

**Additional information** 

Other information : This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D

utilizing the exception found at 49 CFR 173.306.

**ADR** 

No additional information available

Transport by sea

UN-No. (IMDG) : UN1950

Proper Shipping Name (IMDG) : Aerosols, flammable Class (IMDG) : 2.1 - Flammable gases

Air transport

2-propanol

List of Lists)

UN-No.(IATA) : UN1950

Proper Shipping Name (IATA) : Aerosols, flammable
Class (IATA) : 2.1 - Gases : Flammable

## SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

2-propanol (67-63-0)			
Listed on SARA Section 313 (Specific toxic chemic	al listings)		
acetone, propan-2-one, propanone (67-64-1)			
Not listed on SARA Section 313 (Specific toxic chemical listings)			

CAS No 67-63-0

California Proposition 65 - This product does not contain trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

5000 lb

## **SECTION 16: Other information**

RQ (Reportable quantity, section 304 of EPA's

## Full text of H-phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4		
Carc. 1A	Carcinogenicity Category 1A		
Compressed gas	Gases under pressure Compressed gas		
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A		
Flam. Aerosol 2	Flammable aerosol Category 2		
Flam. Gas 1	Flammable gases Category 1		
Flam. Liq. 2	Flammable liquids Category 2		
Muta. 1B	Germ cell mutagenicity Category 1B		
Skin Irrit. 2	Skin corrosion/irritation Category 2		
STOT SE 3	Specific target organ toxicity (single exposure) Category 3		
H220	Extremely flammable gas		
H223	Flammable aerosol		
H225	Highly flammable liquid and vapor		
H280	Contains gas under pressure; may explode if heated		
H302	Harmful if swallowed		
H315	Causes skin irritation		
H319	Causes serious eye irritation		
H336	May cause drowsiness or dizziness		
H340	May cause genetic defects		
H350	May cause cancer		

 Date of issue: 9/1/2015
 Revision date: 05/05/2015
 Version: 1.0
 P GHS SDS
 Page 6 of 7


## Safety Data Sheet

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA reactivity : 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react

with water with some release of energy, but not violently.



## Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.

 Date of issue: 9/1/2015
 Revision date: 05/05/2015
 Version: 1.0
 P GHS SDS
 Page 7 of 7