



From: Avantor Performance Materials, Inc.  
Saucon Valley Plaza  
3477 Corporate Parkway  
Suite #200  
Center Valley, PA 18034



24 Hour Emergency Telephone: 908-859-2151  
CHEMTREC: 1-800-424-9300

National Response in Canada  
CANUTEC: 613-996-6666

Outside U.S. and Canada  
Chemtrec: 703-527-3887

**NOTE:** CHEMTREC, CANUTEC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

All non-emergency questions should be directed to Customer Service, 1-855-AVANTOR (855-282-6867) for assistance.

## NICKEL AMMONIUM SULFATE

### 1. Product Identification

**Synonyms:** Ammonium disulfatonickelote (II) hexahydrate; Ammonium nickel sulfate hexahydrate; Sulfuric acid, ammonium nickel (2+) salt (2:2:1), hexahydrate

**CAS No.:** 15699-18-0

**Molecular Weight:** 395.00

**Chemical Formula:** Ni(NH4)2(SO4)2 6H2O

**Product Codes:** 2760

### 2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous
Nickel Ammonium Sulfate	15699-18-0	90 - 100%	Yes

### 3. Hazards Identification

#### Emergency Overview

**WARNING! HARMFUL IF SWALLOWED OR INHALED. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. MAY CAUSE ALLERGIC SKIN OR RESPIRATORY REACTION. CANCER HAZARD. CAN CAUSE CANCER. Risk of cancer depends on duration and level of exposure.**

**SAF-T-DATA<sup>(tm)</sup>** Ratings (Provided here for your convenience)

Health Rating: 3 - Severe (Cancer Causing)

Flammability Rating: 0 - None

Reactivity Rating: 1 - Slight

Contact Rating: 3 - Severe (Life)

Lab Protective Equip: GOGGLES & SHIELD; LAB COAT & APRON; VENT HOOD; PROPER GLOVES

Storage Color Code: Green (General Storage)

**Inhalation:**

Causes irritation to the respiratory tract. Symptoms may include coughing, sore throat, and shortness of breath. Lung damage may result from a single high exposure or lower repeated exposures. Lung allergy occasionally occurs, with asthma type symptoms.

**Ingestion:**

Toxic. Symptoms may include abdominal pain, diarrhea, nausea, and vomiting. Absorption is poor, but should it occur, symptoms may include giddiness, capillary damage, myocardial weakness, central nervous system depression, and kidney and liver damage.

**Skin Contact:**

Causes irritation. May cause skin allergy with itching, redness or rash. Some individuals may become sensitized to the substance and suffer "nickel itch", a form of dermatitis.

**Eye Contact:**

Causes irritation, redness, and pain.

**Chronic Exposure:**

Prolonged or repeated exposure to excessive concentrations may affect lungs, liver and kidneys. Chronic exposure to nickel and nickel compounds is associated with cancer.

**Aggravation of Pre-existing Conditions:**

Persons with pre-existing skin disorders, impaired respiratory or pulmonary function, or with a history of asthma, allergies, or sensitization to nickel compounds may be at an increased risk upon exposure to this substance.

---

## 4. First Aid Measures

**Inhalation:**

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

**Ingestion:**

Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.

**Skin Contact:**

Immediately flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.

**Eye Contact:**

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

---

## 5. Fire Fighting Measures

**Fire:**

Not considered to be a fire hazard.

**Explosion:**

Not considered to be an explosion hazard.

**Fire Extinguishing Media:**

Use any means suitable for extinguishing surrounding fire.

**Special Information:**

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

---

## 6. Accidental Release Measures

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Sweep up and containerize for reclamation or disposal. Vacuuming or wet sweeping may be used to avoid dust dispersal. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

---

## 7. Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. Areas in which exposure to nickel metal or soluble nickel compounds may occur should be identified by signs or appropriate means, and access to the area should be limited to authorized persons. Wear special protective equipment (Sec. 8) for maintenance break-in or where exposures may exceed established exposure levels. Wash hands, face, forearms and neck when exiting restricted areas. Shower, dispose of outer clothing, change to clean garments at the end of the day. Avoid cross-contamination of street clothes. Wash hands before eating and do not eat, drink, or smoke in workplace. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

---

## 8. Exposure Controls/Personal Protection

### **Airborne Exposure Limits:**

-OSHA Permissible Exposure Limit (PEL):

soluble Nickel compounds as Ni: 1 mg/m<sup>3</sup> (TWA)

-ACGIH Threshold Limit Value (TLV):

soluble Nickel compounds as Ni: 0.1 mg/m<sup>3</sup> (TWA), A4 - Not classifiable as a human carcinogen

### **Ventilation System:**

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

### **Personal Respirators (NIOSH Approved):**

If the exposure limit is exceeded and engineering controls are not feasible, a half facepiece particulate respirator (NIOSH type N95 or better filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest.. A full-face piece particulate respirator (NIOSH type N100 filters) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. **WARNING:** Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

### **Skin Protection:**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

### **Eye Protection:**

Use chemical safety goggles. Maintain eye wash fountain and quick-drench facilities in work area.

### **Other Control Measures:**

Eating, drinking, and smoking should not be permitted in areas where solids or liquids containing soluble nickel compounds are handled, processed, or stored. NIOSH recommends pre-placement and periodic medical exams, with maintaining of records for all employees exposed to nickel in the workplace.

---

## 9. Physical and Chemical Properties

**Appearance:**

Green crystalline solid.

**Odor:**

Odorless.

**Solubility:**

10.4g/100cc in H<sub>2</sub>O @ 20C

**Specific Gravity:**

1.92

**pH:**

4.6 Aqueous solution: (0.1M)

**% Volatiles by volume @ 21C (70F):**

0

**Boiling Point:**

Not applicable.

**Melting Point:**

No information found.

**Vapor Density (Air=1):**

No information found.

**Vapor Pressure (mm Hg):**

No information found.

**Evaporation Rate (BuAc=1):**

No information found.

---

## 10. Stability and Reactivity

**Stability:**

Stable under ordinary conditions of use and storage.

**Hazardous Decomposition Products:**

Emits toxic fumes of nickel, ammonia nitric oxides, and sulfur oxides when heated to decomposition.

**Hazardous Polymerization:**

Will not occur.

**Incompatibilities:**

Aluminum, magnesium, and strong acids.

**Conditions to Avoid:**

Incompatibles.

---

## 11. Toxicological Information

Oral rat LD50: 400 mg/kg. Investigated as a tumorigen.

-----\Cancer Lists\-----			
Ingredient	---NTP Carcinogen---		IARC Category
	Known	Anticipated	
Nickel Ammonium Sulfate (15699-18-0)	No	Yes	1

---

## 12. Ecological Information

**Environmental Fate:**

No information found.

**Environmental Toxicity:**

No information found.

---

## 13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

---

## 14. Transport Information

**Domestic (Land, D.O.T.)**

-----

**Proper Shipping Name:** RQ, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, SOLID, N.O.S.  
(NICKEL AMMONIUM SULFATE)**Hazard Class:** 9**UN/NA:** UN3077**Packing Group:** III**Information reported for product/size:** 300LB

---

## 15. Regulatory Information

```
-----\Chemical Inventory Status - Part 1\-----
Ingredient                                     TSCA  EC   Japan  Australia
-----
Nickel Ammonium Sulfate (15699-18-0)          Yes  Yes  No     No
```

```
-----\Chemical Inventory Status - Part 2\-----
Ingredient                                     Korea  --Canada--
                                     Korea  DSL   NDSL   Phil.
-----
Nickel Ammonium Sulfate (15699-18-0)          Yes   Yes  No     Yes
```

```
-----\Federal, State & International Regulations - Part 1\-----
Ingredient                                     -SARA 302-  -SARA 313-
                                     RQ   TPQ   List  Chemical Catg.
-----
Nickel Ammonium Sulfate (15699-18-0)          No   No    No    Nickel compo
```

```
-----\Federal, State & International Regulations - Part 2\-----
Ingredient                                     CERCLA  -RCRA-  -TSCA-
                                     CERCLA  261.33  8(d)
-----
Nickel Ammonium Sulfate (15699-18-0)          100    No     No
```

Chemical Weapons Convention: No    TSCA 12(b): No    CDTA: No  
SARA 311/312: Acute: Yes    Chronic: Yes    Fire: No    Pressure: No

Reactivity: No (Mixture / Solid)

**WARNING:**

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

**Australian Hazchem Code:** None allocated.

**Poison Schedule:** None allocated.

**WHMIS:**

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

---

## 16. Other Information

**NFPA Ratings:** Health: 2 Flammability: 0 Reactivity: 0

**Label Hazard Warning:**

WARNING! HARMFUL IF SWALLOWED OR INHALED. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. MAY CAUSE ALLERGIC SKIN OR RESPIRATORY REACTION. CANCER HAZARD. CAN CAUSE CANCER. Risk of cancer depends on duration and level of exposure.

**Label Precautions:**

Do not get in eyes, on skin, or on clothing.

Do not breathe dust.

Keep container closed.

Use only with adequate ventilation.

Wash thoroughly after handling.

**Label First Aid:**

If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. In all cases, get medical attention.

**Product Use:**

Laboratory Reagent.

**Disclaimer:**

\*\*\*\*\*  
**THE INFORMATION PRESENTED IN THIS MATERIAL SAFETY DATA SHEET (MSDS/SDS) WAS PREPARED BY TECHNICAL PERSONNEL BASED ON DATA THAT THEY BELIEVE IN THEIR GOOD FAITH JUDGMENT IS ACCURATE. HOWEVER, THE INFORMATION PROVIDED HEREIN IS PROVIDED "AS IS," AND AVANTOR PERFORMANCE MATERIALS MAKES AND GIVES NO REPRESENTATIONS OR WARRANTIES WHATSOEVER, AND EXPRESSLY DISCLAIMS ALL WARRANTIES REGARDING SUCH INFORMATION AND THE PRODUCT TO WHICH IT RELATES, WHETHER EXPRESS, IMPLIED, OR STATUTORY, INCLUDING WITHOUT LIMITATION, WARRANTIES OF ACCURACY, COMPLETENESS, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY, STABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, AND ANY WARRANTIES ARISING FROM COURSE OF DEALING, COURSE OF PERFORMANCE, OR USAGE OF TRADE.**

continued

**THIS MSDS/SDS IS INTENDED ONLY AS A GUIDE TO THE APPROPRIATE PRECAUTIONARY HANDLING OF THE MATERIAL BY A PROPERLY TRAINED PERSON USING THIS PRODUCT, AND IS NOT INTENDED TO BE COMPREHENSIVE AS TO THE MANNER AND CONDITIONS OF USE, HANDLING, STORAGE, OR DISPOSAL OF THE PRODUCT. INDIVIDUALS RECEIVING THIS MSDS/SDS MUST ALWAYS EXERCISE THEIR OWN INDEPENDENT JUDGMENT IN DETERMINING THE APPROPRIATENESS OF SUCH ISSUES. ACCORDINGLY, AVANTOR PERFORMANCE MATERIALS ASSUMES NO LIABILITY WHATSOEVER FOR THE USE OF OR RELIANCE UPON THIS INFORMATION. NO SUGGESTIONS FOR USE ARE INTENDED AS, AND NOTHING HEREIN SHALL BE CONSTRUED AS, A RECOMMENDATION TO INFRINGE ANY EXISTING PATENTS OR TO VIOLATE ANY FEDERAL, STATE, LOCAL, OR FOREIGN LAWS. AVANTOR PERFORMANCE MATERIALS REMINDS YOU THAT IT IS YOUR LEGAL DUTY TO MAKE ALL INFORMATION IN THIS MSDS/SDS AVAILABLE TO YOUR EMPLOYEES.**

\*\*\*\*\*

**Prepared by:** Environmental Health & Safety