

# Windshield Deicer

## Safety Data Sheet



### SECTION 1: Product and company identification

Product name : Windshield Deicer  
Use of the substance/mixture : Aerosol  
Ice melter  
Product code : 820901  
Company : Share Corporation  
P.O. Box 245013  
Milwaukee, WI 53224 - USA  
T (414) 355-4000  
Emergency number : Chemtrec: (800) 424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture


##### GHS-US classification

Flam. Aerosol 1 H222  
Press. Gas (Comp.) H280  
Acute Tox. 3 (Oral) H301  
Acute Tox. 3 (Dermal) H311  
Acute Tox. 3 (Inhalation:gas) H331  
STOT SE 1 H370

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Extremely flammable aerosol  
Contains gas under pressure; may explode if heated  
Toxic if swallowed, in contact with skin or if inhaled  
Causes damage to organs (eyes, Skin, respiratory system, central nervous system, gastro-intestinal tract)

Precautionary statements (GHS-US) :

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Do not spray on an open flame or other ignition source.  
Pressurized container: Do not pierce or burn, even after use.  
Do not breathe fume, mist, spray, vapors.  
Wash thoroughly after handling  
Do not eat, drink or smoke when using this product.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves, protective clothing, eye protection.  
If swallowed: Immediately call a POISON CENTER, a doctor, Do NOT induce vomiting.  
IF ON SKIN: Wash with plenty of soap and water.  
If inhaled: Remove person to fresh air and keep comfortable for breathing  
If exposed: Call a poison center/doctor  
Call a doctor, a POISON CENTER  
Call a POISON CENTER, a doctor if you feel unwell  
Specific treatment (see First aid measures on this label)  
Rinse mouth.  
Take off immediately all contaminated clothing.  
Wash contaminated clothing before reuse.  
Store in a well-ventilated place. Keep container tightly closed.  
Store locked up.  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
Dispose of contents/container to comply with local/regional/national/international regulations.

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable



### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

Full text of H-phrases: see section 16

#### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
methanol	(CAS-No.) 67-56-1	90 - 100	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Lact., H362 Repr. 1B, H360 STOT SE 1, H370
carbon dioxide, liquefied, under pressure	(CAS-No.) 124-38-9	1 - 10	Not classified
1,2-propanediol	(CAS-No.) 57-55-6	1 - 10	Not classified

A specific chemical identity and/or percentage of composition has been withheld as a trade secret. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen if necessary. Respiratory problems: consult a doctor/medical service.
- First-aid measures after skin contact : Rinse skin with water/shower. Soap may be used. Take off contaminated clothing and wash it before reuse. Immediately call a poison center or doctor/physician.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Do NOT induce vomiting. Immediately call a poison center or doctor/physician. Never give anything by mouth to an unconscious person.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : Causes damage to organs. Toxic if swallowed, in contact with skin or if inhaled.
- Symptoms/effects after inhalation : Toxic if inhaled.
- Symptoms/effects after skin contact : Toxic in contact with skin.
- Symptoms/effects after eye contact : May cause severe irritation.
- Symptoms/effects after ingestion : Toxic if swallowed.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Water fog. Dry chemical powder. Carbon dioxide.
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable aerosol. Under fire conditions closed containers may rupture or explode.
- Explosion hazard : Contains gas under pressure; may explode if heated. Bursting aerosol containers may be propelled from a fire at high speed.
- Reactivity : Upon combustion: CO and CO<sub>2</sub> are formed.

#### 5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers.
- Protection during firefighting : Do not attempt to take action without suitable protective equipment.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Evacuate unnecessary personnel. Isolate from fire, if possible, without unnecessary risk. No flames, no sparks. Eliminate all sources of ignition. No open flames. No smoking.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Do not enter without an appropriate protective equipment.
- Emergency procedures : Evacuate unnecessary personnel. No open flames, no sparks, and no smoking.

### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Do not allow to enter drains or water courses.

### 6.3. Methods and material for containment and cleaning up

- For containment : Stop leak if safe to do so. Isolate area until gas has dispersed. Eliminate every possible source of ignition. Use water spray to disperse the vapors. Collect spillage.
- Methods for cleaning up : Take up liquid spill into inert absorbent material.

### 6.4. Reference to other sections

No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use.
- Precautions for safe handling : Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use. Avoid breathing vapors, mist. Use only outdoors or in a well-ventilated area. Do not spray on an open flame or other ignition source.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Do not puncture, incinerate or crush.
- Storage conditions : Store locked up. Keep container tightly closed. Store in a dry place. Store in a well-ventilated place. Keep out of reach of children.
- Incompatible products : Strong acids. alkalis. Oxidizing agents.
- Incompatible materials : Sources of ignition. Heat sources. Open flame.
- Heat-ignition : KEEP SUBSTANCE AWAY FROM: ignition sources. heat sources.
- Storage area : Store in a cool area. Store away from heat. Aerosol 1.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

methanol (67-56-1)		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	250 ppm
ACGIH	Remark (ACGIH)	Headache; eye dam; dizziness; nausea
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
carbon dioxide, liquefied, under pressure (124-38-9)		
ACGIH	ACGIH TWA (ppm)	5000 ppm
ACGIH	ACGIH STEL (ppm)	30000 ppm

### 8.2. Exposure controls

- Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure good ventilation of the work station.
- Personal protective equipment : Use appropriate personal protective equipment when risk assessment indicates this is necessary. Gloves. Protective goggles. Protective apron. Protective clothing. Insufficient ventilation: wear respiratory protection.



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

- Physical state : Gas
- Appearance : Aerosol. Clear, colorless liquid.
- Odor : solvent odor

# Windshield Deicer

## Safety Data Sheet



Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 54 °F (liquid portion - based on lowest flashpoint of the products constituents)
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 0.8 g/ml
Solubility	: Soluble in water.
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
VOC content	: > 95 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Upon combustion: CO and CO<sub>2</sub> are formed.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

### 10.4. Conditions to avoid

Heat. No flames, no sparks. Eliminate all sources of ignition. Welding. Open flame. Direct sunlight.

### 10.5. Incompatible materials

Strong acids. alkalis. Oxidizing agents.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>methanol (67-56-1)</b>	
LD50 dermal rabbit	12800 mg/kg
ATE CLP (oral)	100 mg/kg body weight
ATE CLP (dermal)	300 mg/kg body weight
ATE CLP (vapors)	128.2 mg/l/4h
ATE CLP (dust, mist)	0.5 mg/l/4h
<b>1,2-propanediol (57-55-6)</b>	
LD50 oral rat	22000 mg/kg (Rat, Experimental value)
LD50 dermal rabbit	> 2000 mg/kg body weight (24 h, Rabbit, Experimental value)
ATE CLP (oral)	20000 mg/kg body weight
ATE CLP (dermal)	20800 mg/kg body weight

# Windshield Deicer

## Safety Data Sheet



Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Causes damage to organs (eyes, Skin, respiratory system, central nervous system, gastrointestinal tract).
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Toxic if swallowed. Toxic in contact with skin. Toxic if inhaled.
Symptoms/effects after inhalation	: Toxic if inhaled.
Symptoms/effects after skin contact	: Toxic in contact with skin.
Symptoms/effects after eye contact	: May cause severe irritation.
Symptoms/effects after ingestion	: Toxic if swallowed.
Likely routes of exposure	: Inhalation;Eyes;Dermal;Ingestion

### SECTION 12: Ecological information

#### 12.1. Toxicity

carbon dioxide, liquefied, under pressure (124-38-9)	
LC50 fish 1	35 mg/l (96 h, Salmo gairdneri, Literature study)
1,2-propanediol (57-55-6)	
LC50 fish 1	51600 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Experimental value)
LC50 fish 2	40613 mg/l (Other, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value)
ErC50 (algae)	24200 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value)

#### 12.2. Persistence and degradability

carbon dioxide, liquefied, under pressure (124-38-9)	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable (inorganic)
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
1,2-propanediol (57-55-6)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.96 - 1.08 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.63 g O <sub>2</sub> /g substance
ThOD	1.69 g O <sub>2</sub> /g substance

#### 12.3. Bioaccumulative potential

carbon dioxide, liquefied, under pressure (124-38-9)	
Log Pow	0.83 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
1,2-propanediol (57-55-6)	
BCF other aquatic organisms 1	0.09
Log Pow	-1.07 (Experimental value, EU Method A.8: Partition Coefficient, 20.5 °C)
Bioaccumulative potential	Not bioaccumulative.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). .  
Dispose of contents/container to comply with local/regional/national regulations.

### SECTION 14: Transport information

#### Department of Transportation (DOT)

Transport document description : UN1950 Aerosols flammable, (each not exceeding 1 L capacity), 2.1  
UN-No.(DOT) : UN1950  
Proper Shipping Name (DOT) : Aerosols  
flammable, (each not exceeding 1 L capacity)  
Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115  
Hazard labels (DOT) : 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : None  
DOT Packaging Bulk (49 CFR 173.xxx) : None  
DOT Special Provisions (49 CFR 172.102) : N82  
DOT Packaging Exceptions (49 CFR 173.xxx) : 306  
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg  
DOT Vessel Stowage Location : A  
DOT Vessel Stowage Other : 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

#### Additional information

Other information : When transported by ground, this product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D utilizing the exception found at 49 CFR 173.306. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may be required.

#### ADR

No additional information available

#### Transport by sea

No additional information available

#### Air transport

No additional information available

### SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

methanol	CAS-No. 67-56-1	90 - 100%
methanol (67-56-1)		
Subject to reporting requirements of United States SARA Section 313		
CERCLA RQ	5000 lb	



#### WARNING

This product can expose you to methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

# Windshield Deicer

## Safety Data Sheet



### SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.


Full text of H-phrases:

H225	Highly flammable liquid and vapour
H301	Toxic if swallowed
H311	Toxic in contact with skin
H331	Toxic if inhaled
H360	May damage fertility or the unborn child
H362	May cause harm to breast-fed children
H370	Causes damage to organs

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 4 - Materials that rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and burn readily.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Prepared by: Technical Department

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.*