## **MATERIAL SAFETY DATA SHEET**

1. Product and Company Identification

Product number

CA002

Product name

Pro-Link Chewing Gum Remover

Effective date

14-Oct-2010

Company information

Pro-Link Inc

Canton, MA 02021 United States

Company phone

General Assistance 1-800-74- LINKS

Emergency telephone US

800-424-9300

Emergency telephone outside US

703-527-3887

Version #

07

Supersedes date

15-Oct-2009

### 2. Hazards Identification

Emergency overview

EXTREMELY FLAMMABLE LIQUID AND VAPOR. FLAMMABLE

Aerosol, CONTENTS UNDER PRESSURE.

Will be easily ignited by heat, spark or flames. Harmful in contact with eyes. Can cause adverse reproductive effects - such as birth defects, miscarriages, or infertility. Prolonged exposure may cause chronic effects.

Potential health effects Routes of exposure

Eve contact, Skin contact, Ingestion.

Eyes

Contact may irritate or burn eyes. Eye contact may result in corneal injury.

Skin

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and

Inhalation

Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful.

Ingestion

Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage.

Components of the product may be absorbed into the body by ingestion.

Target organs

Blood, Central nervous system, Liver, Lungs,

Chronic effects

Unconsciousness. Conjunctiva. Cyanosis (blue tissue condition, nails, lips, and/or skin). Liver injury may occur. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Can cause adverse reproductive effects - such as birth defects, miscarriages, or infertility. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May cause delayed lung injury.

Signs and symptoms

Discomfort in the chest. Corneal damage. Narcosis. Cyanosis (blue tissue condition, nails, lips, and/or skin). Coughing, Liver enlargement, Jaundice, Conjunctivitis. Defatting

of the skin. Skin irritation.

3.	Compos	sition /	' Infe	ormation	on	Ingi	edient	S

Components	CAS#	Percent
n-Butane	106-97-8	60 - 70
Propane	74-98-6	20 - 30
Ethyl Alcohol	64-17-5	8 - 10
Non-bazardous and other components below reportable levels		0.0001 - 0.1

### 4. First Aid Measures

First aid procedures

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Continue rinsing. Get medical attention if irritation develops and persists.

Product name: Pro-Link Chewing Gum Remover

MSDS US

Product #: 813-002

Revision date: 14-OCT-2010 Print date: 14-OCT-2010

Skin contact

Remove and isolate contaminated clothing and shoes. Wash off with warm water and soap. Get medical attention if irritation develops and persists. For minor skin contact,

avoid spreading material on unaffected skin.

Inhalation

If symptoms develop move victim to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper

respiratory medical device. Get medical attention, if needed.

Ingestion

If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not induce vomiting without advice from poison control center. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

## 5. Fire Fighting Measures

Flammable properties

Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.

Extinguishing media

Suitable extinguishing media

Foam. Dry chemical. Carbon dioxide (CO2). Do not use water jet.

Protection of firefighters

Protective equipment and

Protective equipment and precautions for firefighters

In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up.

### 6. Accidental Release Measures

Methods for containment

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk.

Methods for cleaning up

Use a non-combustible material like vermiculite, sand or earth to scak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

## 7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Do not get this material in contact with eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin. Avoid prolonged exposure.

Storage

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Do not handle or store near an open flame, heat or other sources of ignition. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs. Level 3 Aerosol.

# 8. Exposure Controls / Personal Protection

#### **Exposure limits**

ACGIH

Components	CAS#	TWA	STEL	Celling
n-Butane	106-97-8	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
Ethyl Alcohol	64-17-5	1000 ppm	1000 ppm	Not established
OSHA				
Components	CAS#	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established
Ethyl Alcohol	64-17-5	1000 ppm	Not established	Not established

#### Personal protective equipment

Eye / face protection Skin protection Do not get in eyes. Chemical goggles are recommended.

Wear appropriate chemical resistant clothing. Chemical resistant gloves.

#### Respiratory protection

Wear positive pressure self-contained breathing apparatus (SCBA). If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

### 9. Physical & Chemical Properties

Appearance Boiling point Compressed liquefied gas. 1.4 °F (-17.2 °C) estimated

Color

clear colorless

Density

0.5699 g/cm3 estimated 41.9597 kJ/g estimated

Flammability (HOC)
Flash back

Yes

Flash point

-156 °F (-104.4 °C) Propellant

Form

Not available Not available

Freezing point

Not availabl

Odor

fruity

Нq

Pressure

Not applicable

Physical state

Liquid. 60 - 70 psig @ 70F

Solubility

Partially

Specific gravity

0.57 estimated

# 10. Chemical Stability & Reactivity Information

Chemical stability

Risk of Ignition.

Conditions to avoid

Heat, flames and sparks.

Hazardous decomposition products

No hazardous decomposition products are known.

## 11. Toxicological Information

#### Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

Ethyl Alcohol

64-17-5

Oral LD50 Rat 7060 mg/kg

n-Butane

106-97-8 74-98-6 Inhalation LC50 Rat 658 mg/L 4 h Inhalation LC50 Rat 658 mg/L 4 h

Propane Sensitization

Not expected to be hazardous by OSHA criteria.

## Carcinogenicity

IARC - Group 1 (Carcinogenic to Humans)

Ethyl Alcohol

64-17-

Monograph 96 [in preparation] (in alcoholic beverages)

Reproductive effects

Hazardous by OSHA criteria. Possible reproductive hazard. Can cause adverse

reproductive effects - such as birth defects, miscarriages, or infertility.

Teratogenicity

Not expected to be hazardous by OSHA criteria.

## 12. Ecological Information

**Ecotoxicity** 

Ecological injuries are not known or expected under normal use.

### 13. Disposal Considerations

Waste codes

D001: Waste Flammable material with a flash point <140 F

Disposal Instructions

Contents under pressure. Do not puncture, incinerate or crush. Dispose of this material and its container to hazardous or special waste collection point. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable

regulations.

Product name: Pro-Link Chewing Gum Remover

MSDS US

# 14. Transport Information

# Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name

Consumer commodity

Hazard class

ORM-D None

Subsidiary hazard class

Additional information:

156, 306

Packaging exceptions Packaging non bulk

156, 306

Packaging bulk

None

#### IMDG

Basic shipping requirements:

Proper shipping name

**AEROSOLS** 

Hazard class

2.1

UN number

1950

Additional information:

Packaging exceptions

LTD QTY

ltem

5F

Labels required

None

Transport Category

2

### ATA

Basic shipping requirements:

Proper shipping name

Aerosols, flammable

Hazard class

2.1

UN number

1950

Additional information:

Packaging exceptions

LTD QTY

Labels required

2.1





# 15. Regulatory Information

US federal regulations

OSHA Process Safety Standard: This material is not known to be hazardous by the

OSHA Highly Hazardous Process Safety Standard, 29 CFR 1910.119.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

CERCLA/SARA Hazardous Substances - Not applicable.

# Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous

Yes

chemical

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely

No

hazardous substance

Section 311 hazardous chemical Yes

Hazard categories (311/312)

immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes

Pressure Hazard - Yes Reactivity Hazard - No

Product name: Pro-Link Chewing Gum Remover

Product #: 813-002 Revision date: 14-OCT-2010 Print date: 14-OCT-2010

#### Inventory status

	Country(s) or region	Inventory name On inventory (yes	s/no)*
	China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
	Europe	European Inventory of New and Existing Chemicals (EINECS)	Yes
	Europe	European List of Notified Chemical Substances (ELINCS)	No
	Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
	Korea	Existing Chemicals List (ECL)	No
	United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

#### State regulations

U.S. - Pennsylvania - RTK (Right to Know) List

 Ethyl Alcohol
 64-17-5
 Present

 n-Butane
 106-97-8
 Present

 Propane
 74-98-6
 Present

# 16. Other Information

Further Information

HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings

Health: 1\* Flammability: 4 Physical hazard: 0

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and

experience currently available.

MSDS sections updated

This document has undergone significant changes and should be reviewed in its entirety.

Prepared by

Regulatory Compliance