

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012. Date of issue: 06/11/2014 Revision date: 06/11/2014 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name : CARB AND CHOKE CLEANER

Product code : 1736

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Carburetor cleaner.

Details of the supplier of the safety data sheet

The Penray Companies, Inc. 440 Denniston Ct. Wheeling, IL 60090 T (800) 373-6729

Manufactured For: Aftermarket Auto Parts Alliance San Antonio, TX 78258 210-492-4868 www.alliance1.com

Emergency telephone number

Emergency number 210-492-4868

CHEMTREC (800) 424-9300

CHEMTREC International +1 (703) 527-3887 24 hr

SECTION 2: Hazards identification

Classification of the substance or mixture

GHS-US classification

Flammable Aerosol 1 Gases Under Pressure - Compressed gas Skin irritation 2 Eye irritation 2A Carcinogenicity 2 Reproductive toxicity 2 (developmental) Specific target organ toxicity - Single exposure 3

Specific target organ toxicity - Repeated exposure 2

Label elements

GHS-US labelling

Hazard pictograms (GHS-US)



GHS02

GHS04





Signal word (GHS-US)

Hazard statements (GHS-US)

: Danger

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. Suspected of damaging the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.

Precautionary statements (GHS-US)

Keep away from heat/sparks/open flames/hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe gas/mist/vapors/spray. If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Protect from sunlight. Do

06/11/2014 EN (English) Page 1

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

6 percent of the mixture consists of ingredient(s) of unknown acute toxicity

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product identifier | % | GHS-US classification |
|------------------------------|--------------------|----------|--|
| Acetone | (CAS No) 67-64-1 | 60 - 100 | Flam. Liq. 2 Eye Irrit. 2A STOT SE 3 |
| Carbon dioxide | (CAS No) 124-38-9 | 5 - 10 | Compressed gas |
| Toluene | (CAS No) 108-88-3 | 3 - 7 | Flam. Liq. 2 Acute Tox. 4 (Oral) Skin Irrit. 2 Repr. 2 STOT SE 3 STOT RE 2 Asp. Tox. 1 |
| Xylenes (o-, m-, p- isomers) | (CAS No) 1330-20-7 | 1 - 5 | Flam. Liq. 3 Acute Tox. 4 (Dermal, Inhalation) Skin Irrit. 2 |
| 2-Butoxyethanol | (CAS No) 111-76-2 | 1 - 5 | Flam. Liq. 3 Acute Tox. 4 (Oral, Dermal, Inhalation) Skin Irrit. 2 Eye Irrit. 2A |
| Phenylethane | (CAS No) 100-41-4 | 0.1 - 1 | Flam. Liq. 2 Acute Tox. 4 (Inhalation) Skin Irrit. 2 Carc. 2 Asp. Tox. 1 |

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.

First-aid measures after ingestion : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause drowsiness, dizziness and central nervous system depression. May cause respiratory tract irritation.

Symptoms/injuries after skin contact : Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Symptoms/injuries after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Symptoms/injuries after ingestion : May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Powder, water spray, foam, carbon dioxide.

06/11/2014 EN (English) 2/7

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

: Do not use a heavy water stream. Unsuitable extinguishing media

Special hazards arising from the substance or mixture 5.2.

Fire hazard : Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides

of carbon.

Explosion hazard Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns

and injuries.

Advice for firefighters 5.3.

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory

protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to General measures

unnecessary and unprotected personnel. Eliminate sources of ignition.

Methods and material for containment and cleaning up 6.2.

For containment : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable

container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal

Protective Equipment (PPE).

: Scoop up material and place in a disposal container. Provide ventilation. Methods for cleaning up

Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

Precautions for safe handling

Precautions for safe handling : Keep away from sources of ignition. - No smoking. Do not spray on an open flame or other

ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/mist/vapors/spray. When using do not eat,

drink or smoke. Use only outdoors or in a well-ventilated area.

: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking. Hygiene measures

Conditions for safe storage, including any incompatibilities 7.2.

Storage conditions : Keep locked up and out of reach of children. Do not expose ot temperatures exceeding 50°C/

122°F. Store away from direct sunlight or other heat sources. Store in a well-ventilated place.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

| Acetone (67-64-1) | | |
|-------------------|------------------------|------------|
| USA ACGIH | ACGIH TWA (ppm) | 500 ppm |
| USA ACGIH | ACGIH STEL (ppm) | 750 ppm |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 2400 mg/m³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 1000 ppm |

| Carbon dioxide (124-38-9) | | |
|---------------------------|------------------------|------------|
| USA ACGIH | ACGIH TWA (ppm) | 5000 ppm |
| USA ACGIH | ACGIH STEL (ppm) | 30000 ppm |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 9000 mg/m³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 5000 ppm |

| Toluene (108-88-3) | | |
|--------------------|--------------------------|---------|
| USA ACGIH | ACGIH TWA (ppm) | 20 ppm |
| USA OSHA | OSHA PEL (TWA) (ppm) | 200 ppm |
| USA OSHA | OSHA PEL (Ceiling) (ppm) | 300 ppm |

06/11/2014 EN (English) 3/7

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

| Xylenes (o-, m-, p- isomers) (1330-20-7) | | |
|--|------------------------|-----------|
| USA ACGIH | ACGIH TWA (ppm) | 100 ppm |
| USA ACGIH | ACGIH STEL (ppm) | 150 ppm |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 435 mg/m³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 100 ppm |

| 2-Butoxyethanol (111-76-2) | | |
|----------------------------|------------------------|-----------|
| USA ACGIH | ACGIH TWA (ppm) | 20 ppm |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 240 mg/m³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 50 ppm |

| Phenylethane (100-41-4) | | |
|-------------------------|------------------------|-----------|
| USA ACGIH | ACGIH TWA (ppm) | 20 ppm |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 435 mg/m³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 100 ppm |

8.2. Exposure controls

Log Pow

Log Kow

Viscosity, kinematic

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below

recommended exposure limits.

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear chemically resistant protective gloves.

Eye protection : Safety glasses or goggles are recommended when using product.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : A NIOSH approved respirator is recommended in poorly ventilated areas or when permissible

exposure limits may be exceeded. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Environmental exposure controls : Maintain levels below Community environmental protection thresholds.

Other information : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully

before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas/Pressurized Liquid.

Appearance : Clear.
Colour : Colourless.
Odour : Solvent.

Odour threshold No data available. pН : No data available. : No data available. Relative evaporation rate (butylacetate=1) Melting point No data available. Freezing point : No data available. Boiling point No data available. Flash point : No data available. Self ignition temperature No data available. Decomposition temperature No data available. Flammability (solid, gas) Flammable. Vapour pressure No data available. Relative vapour density at 20 °C No data available. Relative density 0.880 - 0.884 Solubility No data available.

06/11/2014 EN (English) 4/7

No data available.No data available.

: No data available.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Viscosity, dynamic : No data available.

Explosive properties : No data available.

Oxidising properties : No data available.

Explosive limits : No data available.

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Heat. Incompatible materials. Sources of ignition.

10.5. Incompatible materials

Acids. Amines. Bases. Oxidizers.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

| 1736 | |
|----------------------------|--------------|
| LD50 oral rat | > 2000 mg/kg |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 inhalation rat (mg/l) | > 5 mg/l/4h |

| Acetone (67-64-1) | |
|----------------------------|----------------|
| LD50 oral rat | 5800 mg/kg |
| LC50 inhalation rat (mg/l) | 50100 mg/m³/8h |

| Toluene (108-88-3) | | |
|----------------------------|--------------|--|
| LD50 oral rat | > 5000 mg/kg | |
| LD50 dermal rat | 12124 mg/kg | |
| LD50 dermal rabbit | 8390 mg/kg | |
| LC50 inhalation rat (mg/l) | 28.1 mg/l/4h | |

| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
|--|---------------|
| LD50 oral rat | 4300 mg/kg |
| LD50 dermal rabbit | > 1700 mg/kg |
| LC50 inhalation rat (mg/l) | 47635 mg/l/4h |

| 2-Butoxyethanol (111-76-2) | |
|----------------------------|------------|
| LD50 oral rat | 470 mg/kg |
| LC50 inhalation rat (ppm) | 450 ppm/4h |

| Phenylethane (100-41-4) | | |
|----------------------------|--------------|--|
| LD50 oral rat | 3500 mg/kg | |
| LD50 dermal rabbit | 15354 mg/kg | |
| LC50 inhalation rat (mg/l) | 17.2 mg/l/4h | |

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Based on available data, the classification criteria are not met.

Germ cell mutagenicity : Based on available data, the classification criteria are not met.

06/11/2014 EN (English) 5/7

Safety Data Sheet

| Carcinogenicity | : Suspected of causing cancer. | | |
|--|---|--|--|
| Toluene (108-88-3) | | | |
| IARC group | 3 - Not classifiable | | |
| Xylenes (o-, m-, p- isomers) (1330-20-7) | | | |
| IARC group | 3 - Not classifiable | | |
| 2-Butoxyethanol (111-76-2) | | | |
| IARC group | 3 - Not classifiable | | |
| National Toxicity Program (NTP) Status | 1 - Evidence of Carcinogenicity | | |
| Phenylethane (100-41-4) | | | |
| IARC group | 2B - Possibly carcinogenic to humans | | |
| National Toxicity Program (NTP) Status | Status 1 - Evidence of Carcinogenicity | | |
| Reproductive toxicity | : Suspected of damaging the unborn child. | | |
| Specific target organ toxicity (single exposure) | : May cause drowsiness or dizziness. | | |
| Specific target organ toxicity (repeated exposure) | : May cause damage to organs through prolonged or repeated exposure. | | |
| Aspiration hazard | : Based on available data, the classification criteria are not met. | | |
| Symptoms/injuries after inhalation | : May cause drowsiness, dizziness and central nervous system depression. May cause respirator tract irritation. | | |
| Symptoms/injuries after skin contact | Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin. | | |
| Symptoms/injuries after eye contact | : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. | | |
| Symptoms/injuries after ingestion | : May be harmful if swallowed. May cause stomach distress, nausea or vomiting. | | |
| SECTION 12: Ecological information | | | |
| 12.1. Toxicity | | | |
| Ecology - general | : May cause long-term adverse effects in the aquatic environment. | | |
| 12.2. Persistence and degradability | | | |
| 1736 | | | |
| Persistence and degradability | Not established. | | |
| 12.3. Bioaccumulative potential | | | |
| 1736 | | | |
| Bioaccumulative potential | Not established. | | |
| 2.4. Mobility in soil | | | |

Mobility in soil

No additional information available

12.5. Other adverse effects

: No additional information available Effect on ozone layer

: No known ecological damage caused by this product. Effect on the global warming

SECTION 13: Disposal considerations

Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal

regulations. The generation of waste should be avoided or minimized wherever possible.

Additional information : Flammable vapours may accumulate in the container. Do not incinerate closed containers.

SECTION 14: Transport information

14.1. **UN** number

UN-No. UN1950

14.2. **UN** proper shipping name

Proper Shipping Name : Aerosols, flammable

Hazard Classes

06/11/2014 EN (English) 6/7

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Hazard labels



14.3. Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Acetone (67-64-1)

EPA TSCA Regulatory Flag T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

Toluene (108-88-3)

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting 1.0 %

Xylenes (o-, m-, p- isomers) (1330-20-7)

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting 1.0 %

Phenylethane (100-41-4)

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting 0.1 %

15.2. US State regulations

| 1 | 7 | 3 | 6 |
|---|---|---|---|
|---|---|---|---|

State or local regulations

This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.


SECTION 16: Other information

Indication of changes : None.

Date of issue : 06/11/2014

Other information : None.

NFPA health hazard : 2
NFPA fire hazard : 4
NFPA reactivity : 0



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

06/11/2014 EN (English) 7/7